

### Standard Features

- Poppet valves can be removed with feed lines attached
- Manifolds are used for single On/Off control of fluids including dump valves and solvent feeds
- Easily mountable using NPT threads or block mounting holes
- 1/4" NPT ports standard, larger options available on request
- Uses Autoquip's standard stainless steel cartridge valve




### Technical Specifications

- Fluid Operating Pressure: 300 PSI max (20.68 bar max)
- Air Actuating Pressure: 75-120 PSI (5.2-8.3 bar)
- Trigger Tube Size: 5/32 OD (4mm)
- Fluid Tube Inlet Fitting: Connection Size 1/4" NPT(F)
- Average Flow Rate: 2000cc/min @ 80 psi and 50 centipoise
- Wetted Parts: 304 & 316 stainless steel, PTFE, Delrin, UHMW

### Accessories

Description	Part Number
Repair Kit	3066-50-00A
Setting Gauge	3066-50-01B



# AUTOQUIP 3066

Poppet Color Valve with Non-Piggable Color Stacks

## AQ Non-Piggable Single Color Valve Stacks

CV 3066 - SS-

A	B	C	D	E	F	G
6	1	1	3	0	0	1

### Color Valve

#### "A" Number of Colors

XX = Enter Number of Colors

#### "B" Inlet Size

1 = 1/4"

2 = 3/8"

3 = 1/2"

#### "C" Outlet Size

1 = 1/4" NPT (f)

2 = 3/8" NPT (f)

#### "D" Flush Blocks

0 = None

1 = Solvent Only

2 = Air Only

3 = Solvent and air

#### "E" Check Valves

0 = None

1 = Solvent Check Valve

2 = Air Check Valve

3 = Solvent and Air Check Valve

#### "F" Flush Accessories

0 = None

1 = Air Flush Regulator

2 = Solvent Flush Regulator

3 = Air and Solvent Flush Regulators

#### "G" Mounting Bracket(s)

0 = None

1 = 1

2 = 2

#### Description Example:

**CV 3066-SS-6-113001**

Number of Colors: 6


Inlet Size: 1/4"

Outlet Size: 1/4" NPT (f)

Flush block: Solvent and Air

Flush Accessories: None

Mounting Bracket: 1



[www.aqautomation.com](http://www.aqautomation.com)

N57W13430 Reichert Avenue  
Menomonee Falls, WI 53051  
Ph: 262-781-6133 • Fx 262-781-6188  
sales@aqautomation.com

**AUTOQUIP**  
**AUTOMATION**

